

Designed for commercial and rugged applications, the EX88 Series camera are built for mobile environments that are subject to constant vibration, temperature fluctuation and extreme climate conditions.

EX88-XC5D is a ruggedized versatile camera with adjustable mounting bracket and angle adjustment designed for any indoor, outdoor, rear or side mirror mounting application.

Features:

- 1080P Analog HD (AHD) Resolution
- Sharp and vivid High-Definition video quality
- 80 ° vertical angle and 145° horizontal angle significantly enhances visibility
- Adjustable camera angle and mounting bracket for versatile application
- 6 IR LED for superior image in low light environment
- Rugged metal housing for demanding environment



The EX88-XC Series camera is compatible on all VMDR, XDR series DVR and VPD sensor system



Specifications

Camera (Analog HD)	Sensor	1/29" CMOS 2MP
	Resolution	1920 x 1080 @ 30FPS AHD Analog HD
	Viewing Angle	Horizontal = 145 degrees Vertical = 80 degrees
Housing Material		Metal
Connection		4 Pin DIN connector
Illumination	Minimum	0.1 Lux (IR On) 15ft - 6 IR illuminator
WhiteBalance	Yes	Auto
Auto Gain Control	Yes	Auto
Electronic Shutter	Yes	Auto
S/N Ratio		> 50db
Audio	Mic	No
Environment	Interior / Exterior	Exterior and Interior
Waterproof Level		IP 68

Dimension	(L x W xH)	2.9" x 2.25" x 3.0" (73.66 x 57.15 x 76.2 mm)
Power	Input from System	12VDC +/- 10%
Power	Consumption	165mA / 12VDC +/- 10mA
Temperature	Operating	-4F ~ 131F (-20 ~ +55C)
Humidity	Relative	<90%
Warranty		1 Year Limited Warranty

Specifications subject to change without prior notice - 09 22